



Most Widely Accepted and Trusted

ICC-ES Report

ESR-2980

ICC-ES | (800) 423-6587 | (562) 699-0543 | www.icc-es.org

Reissued 08/2015
This report is subject to renewal 08/2017.

DIVISION: 08 00 00—OPENINGS

SECTION: 08 33 26—OVERHEAD COILING GRILLES

REPORT HOLDER:

THE COOKSON COMPANY, INC.

**2417 SOUTH 50TH AVENUE
PHOENIX, ARIZONA 85043**

EVALUATION SUBJECT:

ACE™ (ACCESS CONTROLLED EGRESS) GRILLE



Look for the trusted marks of Conformity!

“2014 Recipient of Prestigious Western States Seismic Policy Council (WSSPC) Award in Excellence”



ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.



ICC-ES Evaluation Report**ESR-2980**

Reissued August 2015

This report is subject to renewal August 2017.www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS
Section: 08 33 26—Overhead Coiling Grilles**REPORT HOLDER:****THE COOKSON COMPANY, INC.**
2417 SOUTH 50TH AVENUE
PHOENIX, ARIZONA 85043
www.cooksondoor.com**EVALUATION SUBJECT:****ACE™ (ACCESS CONTROLLED EGRESS) GRILLE****1.0 EVALUATION SCOPE****Compliance with the following code:**

- 2009 *International Building Code*® (IBC)
- 2013 *Abu Dhabi International Building Code* (ADIBC)[†]

[†]The ADIBC is based on the 2009 IBC. 2009 IBC code sections referenced in this report are the same sections in the ADIBC.

Property evaluated:

Operating characteristics

2.0 USES

The Cookson Company, Inc., ACE™ (Access Controlled Egress) Grille is an electric-operated vertical rolling grille with emergency response opening capabilities that is used as an alternative access-controlled egress door in interior locations under the provisions of Section 1008.1.4.4 of the IBC, as limited by Section 5.2 of this report.

3.0 DESCRIPTION

The grille consists of a combination of open-air security grille curtain construction with an automatic emergency opening capability. The grille is factory-fabricated in accordance with the approved quality manual, and consists of horizontal rods and vertical links that attach together to form a curtain that coils around a counterbalance shaft while opening. The counterbalance shaft is supported above the opening and secured by two brackets or end plates. The curtain travels in a side member within which the edge of the curtain is supported and guided. When in the closed position, the grille provides a physical barrier and additional security by means of an automatic locking device. Upon activation of the building fire alarm system, if provided, or building automatic fire sprinkler or fire detection system, if present, or power outage or activation of the incorporated panic device, the locking device and operator automatically disengage and the curtain raises to the fully open position to allow emergency egress.

4.0 INSTALLATION

The grille must be installed with an approved entrance and egress access control system in accordance with the manufacturer's published installation instructions, the requirements of IBC Section 1008.1.4.4 and this report.

5.0 CONDITIONS OF USE

The ACE™ (Access Controlled Egress) Grille described in this report complies with, or is a suitable alternative to what is specified in, the code indicated in Section 1.0 of this report, subject to the following conditions:

- 5.1** The grille must be installed with an approved entrance and egress access control system in accordance with the manufacturer's published installation instructions, the requirements of IBC Section 1008.1.4.4 and this report. In the event of conflict between this report and the manufacturer's installation instructions, this report governs.
- 5.2** The rolling grille must not be used as a replacement for a code-required exit door for the area being served, nor shall it be installed at a required exit access door.
- 5.3** The emergency push-button manual unlocking device must be located and identified in accordance with the requirements of Section 1008.1.4.4 of the IBC and Section 703 of ICC/ANSI A117.
- 5.4** All electrical components and the operator for this system must be listed in accordance with the requirements of the *National Electrical Code* NFPA 70.
- 5.5** The installed grilles must be tested and adjusted in accordance with the manufacturer's published installation instructions prior to being placed in operation.

6.0 EVIDENCE SUBMITTED

- 6.1** Manufacturer's published installation instructions and product data sheets.
- 6.2** Data in accordance with the ICC-ES Evaluation Guideline for Electric-operated Vertical Rolling Grilles with Emergency Response Opening Capabilities (EG287), dated March 1, 2005.
- 6.3** A quality control manual.

7.0 IDENTIFICATION

The packaging of the ACE™ (Access Controlled Egress) Grille described in this report is identified with the Cookson Company, Inc., name and address, the product name, and the evaluation report number (ESR-2980). Additionally, each grille must be accompanied by the manufacturer's published installation instructions and the instructions for testing and adjusting the grilles.